

Elcometer 415 Paint & Powder Coating Thickness Gauge



Elcometer 415 Coating Thickness Gauge

At a glance:

- Fast, repeatable & accurate
- Large screen display
- Auto switches between Steel (F) or Aluminium (NF) substrates
- Central Bigfoot™ probe for repeatable results
- On-screen instructions
- Rugged & reliable design

This easy to use, low cost gauge provides a simple, accurate and reliable way to measure coatings on smooth ferrous (steel) and non-ferrous (aluminium) substrates.

This gauge with it's intuitive menu allows you to use it straight out of the box.

- **Fast and accurate reading rate:**
Greater than 60 readings per minute.
- **Large, easy to read display:**
The angled, 'enlarged' display is ideal for viewing from all angles.
- **Simple 'zero cal' feature:**
Complete with factory calibration reset if no access to the uncoated substrate.
- **Auto switches to Ferrous or Non-Ferrous:**
Ideal for measuring paint or powder on both steel and aluminium surfaces.
- **Metric or Imperial measurements:**
Readings can be displayed in microns or mills.
- **Bigfoot™ probe for repeatable results:**
Integral probe with V-groove allows accurate positioning on smooth, flat surfaces.
- **Ergonomic design for maximum comfort:**
Easy to hold gauge allows for regular daily use.
- **On-screen instructions:**
The User is guided through the functions of the gauge - in over 20 languages.
- **Rugged & Reliable:**
Built from ABS plastic, this durable gauge is ideal for the paint & powder coating environment.

Coating Thickness Gauges

Coating thickness gauges are used for the measurement of coatings on all metal surfaces. Digital coating gauges are more accurate, more repeatable and more reproducible than any other coating thickness gauges available on the market today. Mechanical coating gauges are the ideal choice when coating thickness needs to be measured in areas where batteries cannot be used or are difficult to obtain. For example in remote locations, underwater, where dangerous gasses are present, you are looking for a basic coating thickness gauge to measure coatings on ferrous substrates.

Elcometer offer the most comprehensive range of both digital and mechanical coating thickness gauges to meet all you requirements.

Can be used in accordance with:	
BS 5411 (11) (3)	BS 3900 (C5)
BS 5599	BS EN ISO 1461
ISO 2178	ISO 2360
ISO 2808	SSPC-PA2 2004
DIN 50984	DIN 50981
ASTM B 244	ASTM B 499
ASTM D 1400	ASTM D 1186

Range	0 to 1000µm (0 to 40 mils)
Accuracy	±3% or ±3µm (±0.12 mils)
Resolution	1µm (0.1 mils)
Measurement Speed	Greater than 60 readings per minute
Weight	130g (4.1oz)
Dimensions	110 x 75 x 35mm (4.3 x 3 x 1.38")
Operating Temperature (ambient)	0° to 50°C (32° to 120°F)
Maximum Operating Temperature (probe)	80°C (176°F)
Storage Temperature	-10° to 55°C (14° to 130°F)
Case	High impact ABS Plastic
Batteries	2 x LR03 (AAA) alkaline dry batteries or rechargeable equivalents (supplied)
Packing list	Paint & Powder Gauge: Elcometer 415 gauge, 4 x check foils (50, 125, 500 & 1000µm / 2, 5, 20 & 40 mils), soft carry case, batteries and operating instructions Automotive Gauge: Elcometer 415 gauge, 4 x check foils (25, 75, 125 & 250µm / 1, 3, 5 & 10 mils), ferrous checkpiece, non-ferrous checkpiece, soft carry case, batteries and operating instructions
Part Number	Paint & Powder Gauge: A415FNFI1 Automotive Gauge: A415FNFI1AUTO

Spares / Accessories	
Ferrous Coating Thickness Standards, 2 Values (50 & 250µm / 2 & 10mil) with Zero Plate	T995166001
Ferrous Coating Thickness Standards, 4 Values (50, 150, 250 & 500µm / 2, 6, 10 & 20mil) with Zero Plate	T995111261
Non-Ferrous Coating Thickness Standards, 2 Values (50 & 125µm / 2 & 5mil) with Zero Plate	T995166011
Non-Ferrous Coating Thickness Standards, 4 Values (40, 75, 125 & 175µm / 1.6, 3, 5 & 7mil) with Zero Plate	T995111271
Ferrous Checkpiece	T99916925
Non-Ferrous Checkpiece	T99916901
Foil: 25µm / 1mil	T9904170-
Foil: 50µm / 2mil	T9904171-
Foil: 75µm / 3mil	T99011411
Foil: 125µm / 5mil	T9904172-
Foil: 250µm / 10mil	T9904174-
Foil: 500µm / 20mil	T9904175-
Foil: 1000µm / 40mil	T9904176-

Related Products



Ideal for both smooth and rough blast profiled and surfaces, the Elcometer 456 has multiple calibration options for accurate, repeatable readings.

With its large, backlit screen the Elcometer 456 range clearly displays the readings and statistics instantaneously. All menus are available in multiple languages and selected by the User.

The memory can store up to 40,000 readings in 999 batches. Readings can be directly outputted to either a printer or to a PC, making the production of reports quick and easy.

The Elcometer 456 remains one of the most advanced hand held coating thickness gauge on the market today and is available with either Integral probes (built in) or an extensive range of separate plug in probes.

ENGLAND

Elcometer Instruments Ltd
Edge Lane
Manchester M43 6BU

Tel: +44 (0)161 371 6000
Fax: +44 (0)161 371 6010
e-mail: sales@elcometer.com
www.elcometer.com

USA

Elcometer Inc
1893 Rochester Industrial Drive
Rochester Hills Michigan 48309

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com
www.elcometer.com

CANADA

Elcometer Ltd
PO Box 622, 401 Ouelette Avenue
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: ca_info@elcometer.com
www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd
896 Dunearn Rd
Sime Darby Centre #3-09
Singapore 589472,
Republic of Singapore

Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com
www.elcometer.com

BELGIUM

Elcometer SA
Rue Vallée 13
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.be
www.elcometer.be

FRANCE

Elcometer SARL
97 Route de Chécy
45430 BOU

Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.fr
www.elcometer.fr

GERMANY

Elcometer Instruments GmbH
Himmelingstraße 18
D-73434 Aalen

Tel: +49 (0)7366 91 92 83
Fax: +49 (0)7366 91 92 86
e-mail: de_info@elcometer.de
www.elcometer.de